



THE NEW AIRTRONIC 3 PRODUCT FAMILY

AIRTRONIC S3/M3

With the third generation of the Airtronic, Eberspächer is launching a completely new product family of air heaters for commercial and special vehicles.

It combines high heating performance with a very compact design, quiet operation, automatic altitude adjustment up to 5,500 m* and flexible installation. The Eberspächer EasyStart Pro and EasyStart Web control units offer particularly convenient and user-

friendly operation for the Airtronic. All other control units are also compatible.

The Airtronic 3 complements Eberspächer's segment-focused product strategy perfectly, boasting a new combustion chamber concept and other new features, including a new casing design. And of course, the enhancements previously made to the Airtronic 2 are included in the third-generation heaters as well.

EBERSPÄCHER AUS/NZ

Offered by Modular Wholesale Co. Pty Ltd
P.O Box 4313, Dandenong
South, VIC 3164
PH: 1300 770 588 modularw.com.au


MODULAR WHOLESALE
Home of Eberspächer
Australia and New Zealand



 Kalori

Eberspächer

AIR HEATING



ADDITIONAL FEATURES:

- Patented housing design for improved plagiarism protection
- Lifetime of up to 5,000 operating hours due to brushless motor
- Backward compatibility through carry-over connections
- Sensor-controlled, optimized start-up sequences through measurement of environmental parameters
- Optimized heat air flow due to

improved heat exchanger

- Maximum control with EasyStart Pro and EasyStart Web
- Compatibility with all other control units
- Diagnostics and parameter assignment via EasyScan
- Can also be integrated into on-board systems via CAN (12/24V), LIN (12V), S+(12/24V) interfaces

SEGMENTS:



ADVANTAGES:

- High heating power, yet compact design
- Automatic altitude adjustment up to 5,500 m*
- Flexible installation with 90° tilt possible to either side
- Stepless heating performance control ensures quiet operation



TECHNICAL DATA:

	S3 COMMERCIAL		M3 RECREATIONAL	
AIRTRONIC				
FUEL	Diesel		Diesel	
VERSION	D2L		D4R	
VOLTAGE (V)	12	24		12
HEATING CAPACITY (KW)	0.85 - 2.2		1.05 – 4.0	
HEATING AIR FLOW RATE * (kg/h)	max. 105		max. 190	
ELECTRICAL POWER CONSUMPTION (W)	max. 28		max. 55	
FUEL CONSUMPTION (l/h)	0.1 - 0.27		0.12 – 0.49	
OPERATING TEMPERATURE HEATER (°C)	-40 to +70		-40 to +70	
WEIGHT (kg)	2.5		4.4	
MAIN DIMENSIONS LXWXH (mm)	310x115x122		376x140x150	
ORDER NUMBER	25.2953. 05.000	29.2954. 05.0000	25.2957.05.0000	

* depending on the version **without counterpressure with cap «diameter sign» 75 mm

EBERSPÄCHER AUS/NZ

Offered by Modular Wholesale Co. Pty Ltd
 P.O Box 4313, Dandenong
 South, VIC 3164
 PH: 1300 770 588 modularw.com.au



Eberspächer